

Hydrofluoric Acid

Reducing the risk of human exposure.



Used in the production of aluminum, fluorocarbons and gasoline and for applications like glass etching and uranium processing, hydrofluoric acid is an extremely dangerous chemical that must be handled with the utmost care.

- This corrosive liquid penetrates tissue more quickly than typical acids. Toxicity can occur through dermal, ocular, inhalation and oral routes.
- Since HF alters nerve function, accidental exposure can go unnoticed by the victim, delaying treatment and increasing the extent of injury.
- It can also be absorbed by the blood through the skin, reacting with blood calcium and potentially causing a heart attack.

The extreme nature of this chemical calls for superior structural integrity - the level of integrity Poly Processing is known for.

California
8055 S. Ash St.
French Camp, CA 95231

Louisiana
P.O. Box 4150
2201 Old Sterlington Rd.
Monroe, LA 71203
Tel: 866-765-9957
sales@polyprocessing.com
www.polyprocessing.com

Virginia
161 McGhee Rd.
Winchester, VA 22603



The Poly Processing HYDROFLUORIC ACID SYSTEM.

When people's lives are at risk, you can take no chances. You need a system that goes above and beyond to prevent contact with this corrosive acid. That system starts with a cross-linked polyethylene tank. XLPE is a thermoset resin that gives customers **20 times the environmental stress-crack resistance, 10 times the molecular weight and 5 times the impact and tensile strength of HDPE.** This system carries a warranty for a full five years.

A SAFE-Tank® can help **reduce health and environmental concerns** due to closed containment of hydrofluoric acid. If a SAFE-Tank® is not a possibility, an IMFO® tank can be used to **reduce hands-on maintenance**, thereby reducing the risk to your employees.

CHEMICAL	RESIN TYPE	SPECIFIC GRAVITY RATING	FITTING MATERIAL	GASKET MATERIAL	BOLT MATERIAL
Hydrofluoric Acid	XLPE	1.9	PP	Viton®	C-276

» See our website for a complete Chemical Resistance Chart.

Tank Specifications & Technical Overview

IMFO® VERTICAL FLAT BOTTOM OF XLPE:

- 230-15,500 gallons
- 1.9 spg rating

NON-IMFO® ALTERNATIVES:

SAFE-Tank® XLPE:

- 55-8,700 gallons
- 1.9 spg rating for primary tank
- Spg ratings for secondary tanks ≥ 3,000 gallons may be equal to or 1 less spg than primary tank
- All other tank sizes must equal primary tank spg rating

Standard Vertical Flat Bottom XLPE:

- 30-15,500 gallons
- 1.9 spg rating

Alternative secondary containment: PPC secondary containment basin or other secondary containment suitable for hydrofluoric acid, of adequate size for use.

Plumbing: Requires use of flexible connections with fittings on lower one-third of sidewall. See page 80 for flexible connections options.

Venting: Go to www.polyprocessing.com/venting for venting information.

Foundation: PPC IMFO® tank pad or smooth concrete foundation designed to accommodate IMFO®, SAFE-Tank® or vertical tank.

Temperature: Product should not exceed 100°F at delivery or during storage to maintain ASTM D 1998 design parameters.

Lid: Fume-tight manway cover to manage release of chemical gases.

Options: Restraint systems for wind and seismic, level gauges, ladders, heating pads, insulation, mixer mounts and engineering stamp.

The above components are just a few of the many options offered by Poly Processing. For additional information and products visit www.polyprocessing.com/hydrofluoricacid or talk to your Poly Processing representative.

