

1. MANWAY & COVER WITH RADIUS FLANGE FOR ATTACHMENT TO THE SIDEWALL OF A TANK

2. 1/4" THICK GASKETS FOR SEALING THE MANWAY TO THE TANK EXTERNALLY AND THE ATTACHMENT HARDWARE TO THE TANK INTERNALLY


3. 1/2" X 4-1/2" PE ENCAPSULATED STUD BOLTS FOR ATTACHING THE MANWAY TO THE TANK

**MATERIALS:**  
 FIBERGLASS\*  
 304SS  
 316SS  
 C-276 (HASTELLOY)  
 TITANIUM

**GASKETS:**  
 EPDM\*  
 VITON

**ATTACHMENT HARDWARE:**  
 316SS\*  
 C-276 (HASTELLOY)  
 TITANIUM

CONFIDENTIAL PROPERTY OF  
 POLY PROCESSING COMPANY  
 NOT FOR REPRINT OR USE  
 WITHOUT PERMISSION

DWG TITLE			
SIDE MANWAY / FRP / 24INCH			
SCALE:	2"=1'-0"	 Central Region P.O. Box 4159 (71211) 8901 Old Sterlington Rd. Monroe, LA 71203 (504) 343-7565 FAX (504) 343-8795	DR:
DATE:	9/13/13		CK:
		SHEET	COMPUTER FILE
		1 OF 1	24SIDEMWYFRP
			REV
			A