

Poly Processing Company
 Incremental Capacity Sheet for Upright Tanks

Tank: 2000 Gallons, Upright
 Print Date: 10/22/19

Outside Diameter = 85.00 in
 Shell Length = 84.00 in
 Calculated Capacity = 2035 gal

| Inches | Gallons | Inches | Gallons | Inches | Gallons |
|--------|---------|--------|---------|--------|---------|
| 1 | 24 | 41 | 993 | 81 | 1962 |
| 2 | 48 | 42 | 1018 | 82 | 1987 |
| 3 | 73 | 43 | 1042 | 83 | 2011 |
| 4 | 97 | 44 | 1066 | 84 | 2035 |
| 5 | 121 | 45 | 1090 | | |
| 6 | 145 | 46 | 1114 | | |
| 7 | 170 | 47 | 1139 | | |
| 8 | 194 | 48 | 1163 | | |
| 9 | 218 | 49 | 1187 | | |
| 10 | 242 | 50 | 1211 | | |
| 11 | 266 | 51 | 1236 | | |
| 12 | 291 | 52 | 1260 | | |
| 13 | 315 | 53 | 1284 | | |
| 14 | 339 | 54 | 1308 | | |
| 15 | 363 | 55 | 1332 | | |
| 16 | 388 | 56 | 1357 | | |
| 17 | 412 | 57 | 1381 | | |
| 18 | 436 | 58 | 1405 | | |
| 19 | 460 | 59 | 1429 | | |
| 20 | 485 | 60 | 1454 | | |
| 21 | 509 | 61 | 1478 | | |
| 22 | 533 | 62 | 1502 | | |
| 23 | 557 | 63 | 1526 | | |
| 24 | 581 | 64 | 1550 | | |
| 25 | 606 | 65 | 1575 | | |
| 26 | 630 | 66 | 1599 | | |
| 27 | 654 | 67 | 1623 | | |
| 28 | 678 | 68 | 1647 | | |
| 29 | 703 | 69 | 1672 | | |
| 30 | 727 | 70 | 1696 | | |
| 31 | 751 | 71 | 1720 | | |
| 32 | 775 | 72 | 1744 | | |
| 33 | 799 | 73 | 1769 | | |
| 34 | 824 | 74 | 1793 | | |
| 35 | 848 | 75 | 1817 | | |
| 36 | 872 | 76 | 1841 | | |
| 37 | 896 | 77 | 1865 | | |
| 38 | 921 | 78 | 1890 | | |
| 39 | 945 | 79 | 1914 | | |
| 40 | 969 | 80 | 1938 | | |

NOTE: The above values are not intended for input or output metering.